## COMPACT LOADERS Specifications

MODEL	SL750	TL750
ENGINE		
Туре	KIOTI	
Horsepower	73.6 hp (54.9 kW)	
HYDRAULIC SYSTEM		
Loader Hydraulic Pressure	3,335 psi (230 bar)	
Auxiliary Standard Flow	21.9 gpm (82.9 lpm)	
PERFORMANCE		
Tipping Load	5,380 lbs. (2,440 kg)	6,570 lbs. (2,980 kg)
Rated Operating Capacity	2,689 lbs. (1,220 kg)	2,300 lbs. (1,043 kg)
35% Tipping Load	1,883 lbs. (854 kg)	2,300 lbs. (1,043 kg)
50% Tipping Load	2,689 lbs. (1,220 kg)	3,285 lbs. (1,490 kg)
Travel Speed : LOW	7.15 mph (11.5 kph)	4.7 mph (7.5 kph)
Travel Speed : HIGH	12.05 mph (19.4 kph)	7.1 mph (11.5 kph)
Operating Weight	8,362 lbs. (3,793 kg)	9,689.3 lbs. (4,395 kg)
DIMENSIONS		
Lift Height to Hinge Pin	126.6 in. (3,215 mm)	130.3 in. (3,310 mm)
Length w/o Attachment	116.5 in. (2,960 mm)	
Width Over Tires/Tracks	71.7 in. (1,820 mm)	70.9 in. (1,800 mm)
Height to Top of Cab	81.2 in. (2,063 mm)	81.9 in. (2,080 mm)
Wheelbase	47.2 in. (1,200 mm)	N/A

NOTE: Specifications and design are subject to change without notice.

## **STANDARD EQUIPMENT**


- LED Front and Rear Work Lights
- Hydraulic Pilot Joystick
- Overhead Sliding Front Door
- In-Cab Display
- Auxiliary Hydraulics
- Suspension Seat
- 2" Seat Belt
- Self-Leveling
- 2-Speed
- 14-Pin Electrical Connector

## **OPTIONAL EQUIPMENT**

- Ride Control
- HVAC
- Bluetooth Radio
- Power Quick Attach
- 3" Seat Belt







KIOTI.com LIT-CCE-SPEC-1